

HYDRAULIC PULLER

www.aeroboom.com
info@aeroboom.com

HYDRAULIC PULLER 5 to 50 Tons

www.aeroboom.com
info@aeroboom.com

Posi Lock's hydraulic pullers are the preferred choice of professionals around the world. Ideal for many uses, Posi Lock adds efficiency to a job that can often be frustrating and labor intensive. Posi Lock hydraulic pullers are available in 2- or 3-jaw models and range from 5- to 100-ton capacity. Known for safety, high quality, durability, and ease of use, our pullers are designed to help you extend bearing life in your applications through proper installation, removal and service.

PHA Series

Contains: Puller Iron, Ram Points, Lift Plate



Model Number	Capacity Tons	Number of Jaws	Reach in. (mm)	Spread in. (mm)	Optional Long Jaws	Reach with Long Jaws in. (mm)	Spread with Long Jaws in. (mm)	Optional Accessories		
								Optional Leveling Arm Bracket Set	Optional Hydraulic Lift Cart	Optional Storage Transport Cart
PHA-206	5	2	6 in. (152.4 mm)	.5 to 8 in. (12.7 to 203.2 mm)	—	—	—	—	—	—
PHA-106	5	3	6 in. (152.4 mm)	.5 to 8 in. (12.7 to 203.2 mm)	—	—	—	—	—	—
PHA-208	10	2	8 in. (203 mm)	.75 to 12 in. (19 to 305 mm)	11054/11054L	9.8 in. (249 mm)/16 in. (406 mm)	2.3 to 15.8 in. (58 to 401 mm)/1.5 to 22 in. (38 to 559 mm)	—	—	—
PHA-108	10	3	8 in. (203 mm)	.75 to 12 in. (19 to 305 mm)	11054/11054L	9.8 in. (249 mm)/16 in. (406 mm)	2.3 to 15.8 in. (58 to 401 mm)/1.5 to 22 in. (38 to 559 mm)	—	—	—
PHA-210	15	2	10 in. (254 mm)	1 to 15 in. (25 to 381 mm)	11054L	16 in. (406 mm)	1.5 to 22 in. (38 to 559 mm)	PH-1210	—	—
PHA-110	15	3	10 in. (254 mm)	1 to 15 in. (25 to 381 mm)	11054L	16 in. (406 mm)	1.5 to 22 in. (38 to 559 mm)	PH-1110	—	—
PHA-213	25	2	12 in. (305 mm)	2.5 to 18 in. (64 to 457 mm)	11354L	20 in. (508 mm)	1.5 to 30 in. (38 to 762 mm)	PH-1213	PT-3050	PT-2550
PHA-113	25	3	12 in. (305 mm)	2.5 to 18 in. (64 to 457 mm)	11354L	20 in. (508 mm)	1.5 to 30 in. (38 to 762 mm)	PH-1113	PT-3050	PT-2550
PHA-216	50	2	14 in. (356 mm)	3 to 25 in. (76 to 635 mm)	PH-21654L	26 in. (660 mm)	2 to 38 in. (51 to 965 mm)	PH-1216	PT-3050	PT-2550
PHA-116	50	3	14 in. (356 mm)	3 to 25 in. (76 to 635 mm)	PH-11654L	26 in. (660 mm)	2 to 38 in. (51 to 965 mm)	PH-1116	PT-3050	PT-2550

PHB Series

Contains: Puller Iron, Ram Points, Lift Plate, Hydraulic Cylinder



Model Number	Capacity Tons	Number of Jaws	Reach in. (mm)	Spread in. (mm)	Optional Long Jaws	Reach with Long Jaws in. (mm)	Spread with Long Jaws in. (mm)	Optional Leveling Arm Bracket Set	Optional Hydraulic Lift Cart	Optional Storage Transport Cart
PHB-106	5	3	6 in. (152.4 mm)	.5 to 8 in. (12.7 to 203.2 mm)	—	—	—	—	—	
PHB-208	10	2	8 in. (203 mm)	.75 to 12 in. (19 to 305 mm)	11054/11054L	9.8 in. (249 mm)/16 in. (406 mm)	2.3 to 15.8 in. (58 to 401 mm)/1.5 to 22 in. (38 to 559 mm)	—	—	—
PHB-108	10	3	8 in. (203 mm)	.75 to 12 in. (19 to 305 mm)	11054/11054L	9.8 in. (249 mm)/16 in. (406 mm)	2.3 to 15.8 in. (58 to 401 mm)/1.5 to 22 in. (38 to 559 mm)	—	—	—
PHB-210	15	2	10 in. (254 mm)	1 to 15 in. (25 to 381 mm)	11054L	16 in. (406 mm)	1.5 to 22 in. (38 to 559 mm)	PH-1210	—	—
PHB-110	15	3	10 in. (254 mm)	1 to 15 in. (25 to 381 mm)	11054L	16 in. (406 mm)	1.5 to 22 in. (38 to 559 mm)	PH-1110	—	—
PHB-213	25	2	12 in. (305 mm)	2.5 to 18 in. (64 to 457 mm)	11354L	20 in. (508 mm)	1.5 to 30 in. (38 to 762 mm)	PH-1213	PT-3050	PT-2550
PHB-113	25	3	12 in. (305 mm)	2.5 to 18 in. (64 to 457 mm)	11354L	20 in. (508 mm)	1.5 to 30 in. (38 to 762 mm)	PH-1113	PT-3050	PT-2550
PHB-216	50	2	14 in. (356 mm)	3 to 25 in. (76 to 635 mm)	PH-21654L	26 in. (660 mm)	2 to 38 in. (51 to 965 mm)	PH-1216	PT-3050	PT-2550
PHB-116	50	3	14 in. (356 mm)	3 to 25 in. (76 to 635 mm)	PH-11654L	26 in. (660 mm)	2 to 38 in. (51 to 965 mm)	PH-1116	PT-3050	PT-2550

PHMS Series

Contains: Puller Iron, Ram Points, Lift Plate, Hydraulic Cylinder, Manual Pump, Gauge Adapter, 10,000 PSI Gauge, Male Coupler with dust cap, 10-foot heavy-duty Hose



Model Number	Capacity Tons	Number of Jaws	Reach in. (mm)	Spread in. (mm)	Optional Long Jaws	Reach with Long Jaws in. (mm)	Spread with Long Jaws in. (mm)	Optional Leveling Arm Bracket Set	Optional Hydraulic Lift Cart	Optional Storage Transport Cart
PHMS-106	5	3	6 in. (152.4 mm)	.5 to 8 in. (12.7 to 203.2 mm)	—	—	—	—	—	
PHMS-208	10	2	8 in. (203 mm)	.75 to 12 in. (19 to 305 mm)	11054/11054L	9.8 in. (249 mm)/16 in. (406 mm)	2.3 to 15.8 in. (58 to 401 mm)/1.5 to 22 in. (38 to 559 mm)	—	—	—
PHMS-108	10	3	8 in. (203 mm)	.75 to 12 in. (19 to 305 mm)	11054/11054L	9.8 in. (249 mm)/16 in. (406 mm)	2.3 to 15.8 in. (58 to 401 mm)/1.5 to 22 in. (38 to 559 mm)	—	—	—
PHMS-210	15	2	10 in. (254 mm)	1 to 15 in. (25 to 381 mm)	11054L	16 in. (406 mm)	1.5 to 22 in. (38 to 559 mm)	PH-1210	—	—
PHMS-110	15	3	10 in. (254 mm)	1 to 15 in. (25 to 381 mm)	11054L	16 in. (406 mm)	1.5 to 22 in. (38 to 559 mm)	PH-1110	—	—
PHMS-213	25	2	12 in. (305 mm)	2.5 to 18 in. (64 to 457 mm)	11354L	20 in. (508 mm)	1.5 to 30 in. (38 to 762 mm)	PH-1213	PT-3050	PT-2550
PHMS-113	25	3	12 in. (305 mm)	2.5 to 18 in. (64 to 457 mm)	11354L	20 in. (508 mm)	1.5 to 30 in. (38 to 762 mm)	PH-1113	PT-3050	PT-2550
PHMS-216	50	2	14 in. (356 mm)	3 to 25 in. (76 to 635 mm)	PH-21654L	26 in. (660 mm)	2 to 38 in. (51 to 965 mm)	PH-1216	PT-3050	PT-2550
PHMS-116	50	3	14 in. (356 mm)	3 to 25 in. (76 to 635 mm)	PH-11654L	26 in. (660 mm)	2 to 38 in. (51 to 965 mm)	PH-1116	PT-3050	PT-2550

PHES Series

Contains: Puller Iron, Ram Points, Lift Plate, Hydraulic Cylinder, 2 Stage Electric Pump, Gauge Adapter, 10,000 PSI Gauge, Male Coupler with dust cap, 10-foot heavy-duty Hose



Model Number	Capacity Tons	Number of Jaws	Reach in. (mm)	Spread in. (mm)	Optional Long Jaws	Reach with Long Jaws in. (mm)	Spread with Long Jaws in. (mm)	Optional Leveling Arm Bracket Set	Optional Hydraulic Lift Cart	Optional Storage Transport Cart
PHES-106	5	3	6 in. (152.4 mm)	.5 to 8 in. (12.7 to 203.2 mm)	—	—	—	—	—	
PHES-208	10	2	8 in. (203 mm)	.75 to 12 in. (19 to 305 mm)	11054/11054L	9.8 in. (249 mm)/16 in. (406 mm)	2.3 to 15.8 in. (58 to 401 mm)/1.5 to 22 in. (38 to 559 mm)	—	—	—
PHES-108	10	3	8 in. (203 mm)	.75 to 12 in. (19 to 305 mm)	11054/11054L	9.8 in. (249 mm)/16 in. (406 mm)	2.3 to 15.8 in. (58 to 401 mm)/1.5 to 22 in. (38 to 559 mm)	—	—	—
PHES-210	15	2	10 in. (254 mm)	1 to 15 in. (25 to 381 mm)	11054L	16 in. (406 mm)	1.5 to 22 in. (38 to 559 mm)	PH-1210	—	—
PHES-110	15	3	10 in. (254 mm)	1 to 15 in. (25 to 381 mm)	11054L	16 in. (406 mm)	1.5 to 22 in. (38 to 559 mm)	PH-1110	—	—
PHES-213	25	2	12 in. (305 mm)	2.5 to 18 in. (64 to 457 mm)	11354L	20 in. (508 mm)	1.5 to 30 in. (38 to 762 mm)	PH-1213	PT-3050	PT-2550
PHES-113	25	3	12 in. (305 mm)	2.5 to 18 in. (64 to 457 mm)	11354L	20 in. (508 mm)	1.5 to 30 in. (38 to 762 mm)	PH-1113	PT-3050	PT-2550
PHES-216	50	2	14 in. (356 mm)	3 to 25 in. (76 to 635 mm)	PH-21654L	26 in. (660 mm)	2 to 38 in. (51 to 965 mm)	PH-1216	PT-3050	PT-2550
PHES-116	50	3	14 in. (356 mm)	3 to 25 in. (76 to 635 mm)	PH-11654L	26 in. (660 mm)	2 to 38 in. (51 to 965 mm)	PH-1116	PT-3050	PT-2550

Hydraulic Pullers

Hydraulic Pullers