

SIDEWINDER JACKS

Mini jacks
5-20 Ton Capacity



▶ FEATURES

- Retracted height of just 63.5mm for the smallest jack and 130.2 mm for the 20 ton, allows you to slip this jack into the narrowest of crevices.
- Jacks operate either horizontally or vertically. Handles function in line with base for easier use in confined spaces.
- The perfect addition to any toolbox, this remarkable little jack has multiple uses that are limited only by your imagination. Use it as a jack or a spreader. Use it to turn your mechanical gear puller (puller capacity must match jack capacity) into a hydraulic puller. Use it vertically or horizontally in limited clearance.Z



Bottle Jacks
Sidewinder Jack

TECHNICAL DATA*

Model Number	Cap. (tons)	Stroke (mm)	Retracted Height Min. (mm)	Max Height (mm)	No. Pump Strokes to Ext. Piston 25 (mm)	Saddle Dia. (mm)	Base Size Dia. (mm)	Pump Handle Length (mm)	Handle Effort at Rated Cap. (kg)	Carry Handle	Product Weight (kg)
AB-9105	5	19	63.5	85.7	30	29	73.8	240	26	No	1.9
AB-9205	5	38	88.9	130.2	38	29	73.8	240	26	No	2.4
AB-9210	10	30	120.7	149.2	36	42.1	109.9	440	28	No	5.5
AB-9220	20	30	130.2	160.3	46	52.8	119.9	605	35	No	8

*See current price list for shipping weights.