

ATJ Series

2-25 TON

FEATURES | ATJ-1 SERIES

- Complies with ANSI/ASME B30.1, CE/GS standards.
- Designed for lifting loads with very low minimum clearance (foot) or high clearance (head).
- Can be used in confined spaces.
- Built in safety valve for overload protection.
- Features spring assisted return and over travel protection on 5 and 10 ton models.
- Forged base and cylinder to assure strength.



ATJ-105, ATJ-102



Bottle Jack

Model	Capacity (Ton)		Minimum Height (mm)		Maximum Height (mm)		Weight Kg
	Toe	Head	Toe	Head	Toe	Head	
ATJ-102	2	3	16	238	128.5	349	8
ATJ-105	5	6	22	298.45	141.4	409.5	24
ATJ-110	10	14	28.5	333.5	173	460.5	37.9

FEATURES | ATJ-2 SERIES

- Complies with ANSI/ASME B30.1, CE/GS standards.
- Compact and stable construction.
- Housing revolves 360°.
- Lowering speed can be accurately adjusted.
- Safety valve for overload protection.



ATJ-210, ATJ-205



Toe Jack

Model	Capacity (Ton)		Minimum Height (mm)		Maximum Height (mm)		Weight Kg
	Toe	Head	Toe	Head	Toe	Head	
ATJ-205	5	-	24.9	368	230.1	572	24.9
ATJ-210	10	-	25	420.1	260	650	34.9
ATJ-225	25	-	57.9	504.9	272	720	101.78