

## HYDRAULIC HAND OPERATED COMBINED TOOL

Hand operated portable combi-tool is special rescue tool integrating hydraulic spreader, cutter and hydraulic hand pump, different works, including cutting, spreading and clamping, can be well done by it, it is characterized of compact structure, easy operation and light weight.

**Application:** 1. Traffic accident rescue, earthquake disaster relief and accident rescue etc.;  
2. Unclenching the door and metal structure into deformation;  
3. Cut metal structure, vehicle parts, pipeline and metal plates

**Features:** 1. Blade made of high strength alloy which can be regrind. 2. Body is of high strength aluminum alloy with ceramic coating surface, light and durable. 3. Unique designed handle of new material, convenient to operate. 4. Blade can rotate 360 degree for different rescue requirements. 5. Can be applied in circumstances of underwater and exploding surroundings.

AGYJKB-63-25/20-A



## NEW BIG HYDRAULIC HAND OPERATED COMBINED TOOL

NEW BIG Hand operated portable combi-tool is special rescue tool integrating hydraulic spreader, cutter and hydraulic hand pump, different works, including cutting, spreading and clamping, can be well done by it, it is characterized of compact structure, easy operation and light weight.

**Application:** 1. Traffic accident rescue, earthquake disaster relief and accident rescue etc.;  
2. Unclenching the door and metal structure into deformation;  
3. Cut metal structure, vehicle parts, pipeline and metal plates

**Features:** 1. Blade made of high strength alloy which can be regrind. 2. Body is of high strength aluminum alloy with ceramic coating surface, light and durable. 3. Unique designed handle of new material, convenient to operate. 4. Blade can rotate 360 degree for different rescue requirements. 5. Can be applied in circumstances of underwater and exploding surroundings.

AGYJKB-72-30/22-B



### TECHNICAL PARAMETERS

Model	AGYJKB-63-25/20-A		AGYJKB-72-30/22-B	
Rated Working Pressure	720Bar	10440psi	720Bar	10440psi
Opening Distance of Blades	160mm	6.3in	255mm	10in
Max. Cutting Capacity (Q235 steel)	10mm (steel plate) Φ20mm (circle steel)	0.4in (steel plate) Φ0.8in (circle steel)	10mm (Steel plate) Φ24mm (Circle steel)	0.4 in.(Steel Plate) Φ0.96 in.(Circle Steel)
Max. Cutting Force	300KN	67500 lbs	207KN	46575lbs
Rated Spreading Force	25KN	5600 lbs	190KN	42750lbs
Weight	10kg	22 lbs	11.8kg	26lbs
Dimension(L*W*H)	7350*212*146mm	29*8.3*5.7 in.	825*208*175mm	33*8.3*7 in