



PORTABLE DOOR BREAKING KIT (SIX)

1. Portable Door Breaking Kit (six) including crowbar, hand pump, micro-spreader, edge lifting tool, rebar cutter, micro-cutter; 2. With the function of Chisel, hammer, hiefn, out stapes, spread, lift, split, cut, quick break etc. 3. The tools are put in the toolkit that is beneficial to carry by one person, superior maneuverability; 4. All of the components are made of high strength alloy, light weight, high strength.

Application: 1, mainly used for breaking operation of roller shutter door, security door security window. 2. More suitable for breaking with the requirement of no noise.

Features: 1. Single oil tube, single-hand operation, small size, light weight, easy to use, convenient and fast; 2. Its power source is Mirco-hand pump which is light and efficient; 3. The tools are put in the toolkit that is beneficial to carry by one person, superior maneuverability; 4. The crowbar has the function of Chisel, hammer, hiefn, out stapes, easy to use; 5. The bottom feet of edge lifting tool and piral groove of oil cylinder can increase the opening distance, meet the needs of different angles; 6. The separating tank of edge lifting tool with anti-skidding function, can detach the frame structure which is easy to skid; 7. The micro-cutter with small size, light weight, strong shearing force; 8. The interfaces of the kit tools adopt single hose-planar interface, with the lock function and dust-proof device; 9. All of the components are made of high strength alloy, light weight, high strength.

TECHNICAL PARAMETERS WITH TOOLS

<p>Hydraulic Hand Pump Model : ABS63/0.8-B Rated Working Pressure: 72Mpa Output Pressure(Low Pressure): 5-10MPa Low Pressure Flow =7.5ml/time High Pressure Flow =0.83ml/time Tank Volume of Hydraulic Oil =0.7L Max. Force of Hand Bar =260N Weight =3.2kg Dimension(L*W*H) 400*120*160mm</p>		<p>Hydraulic Door Opener Model AGYKM-63-60/100-W Rated Working Pressure: 72Mpa Closed Length: =210mm Opening Distance 180mm Separation Distance 230mm Lifting Distance 300mm Separation Force 50KN Lifting Force 60KN Weight =3.9kg Dimension(L*W*H) 210*135*75mm</p> 
<p>Model : AWXPC-4A Crow bar Length:457mm Weight:1.8KG</p> 	<p>Micro-Hydraulic Spreader Model : AGYKZ-42/150-W Rated Working Pressure : 72Mpa Opening Distance: =152mm Separation Force: 42KN Weight : =3.3kg Dimension(L*W*H) 345*160*75mm</p>	
<p>AGYSD-63-14/28-A</p> 	<p>Hydraulic Rebar Cutter Model AGYSD-63-14/28-A & AGYJQ-36-18/60 Rated Working Pressure: 720Bar Max. Opening Distance of Blades: =28mm Max. Cutting Capacity: Φ14 & Φ18mm(circle steel) Weight 2.5 & 3kg Dimension(L-300 &350 *W-68 & 105*H-55 & 75mm.</p>	<p>AGYJQ-36-18/60</p> 